

913047 真空燃油管 VACUPRESS OIL

双层热塑性 PVC, PU, 丁晴橡胶混合材料, 内嵌镀锌钢丝螺旋、聚酯纤维层加强, 用于抽吸和输送石油、蓝油, 柴油, 生物柴油。



Two-layer hose in thermoplastic PVC, PU, NITRILE RUBBER compound with embedded galvanised steel spiral with polyester yarn reinforcement for suction and delivery of oils, blue diesel, diesel, bio diesel.

商品详情

| | |
|------------------------------|------------------------------|
| 表面平滑度 SMOOTH SURFACE | ***** |
| 柔韧性能 FLEXIBILITY | ***** |
| 耐磨性能 ABRASION RESISTANCE | ISO 4649:<90 mm ³ |
| 适用温度范围 TEMPERATURE RANGE | -25°C + 60°C |
| 抗化学物质 CHEMICAL RESISTANCE | tabella PVC 石油 |
| 抗压性能 CRUSHING RESISTANCE | *** |

| 内径 ID Inc | 内径 ID mm | 外径 OD mm | 重量 WEIGHT g/m | 弯曲半径 BENDING RADIUS m/m | 工作压力 WORKING PRESS bar | 爆破压力 BURSTING PRESS bar | 真空度 VACUUM m H2O | 每卷长度 COIL LENGTH mt |
|-----------------|----------------|----------------|---------------------|----------------------------------|---------------------------------|----------------------------------|------------------------|------------------------------|
| 3/4 | 19 | 28 | 450 | 70 | 16 | 48 | 9 | 60 |
| 1 | 25 | 35.5 | 670 | 80 | 16 | 48 | 9 | 60 |
| | 30 | 40.6 | 770 | 90 | 16 | 48 | 9 | 60 |
| 1 1/4 | 32 | 42.5 | 800 | 100 | 16 | 48 | 9 | 60 |

| | | | | | | | | |
|-----------------|----|----|------|-----|----|----|---|----|
| | 35 | 48 | 1050 | 120 | 14 | 42 | 9 | 60 |
| $\frac{1}{1/2}$ | 38 | 51 | 1200 | 125 | 14 | 42 | 9 | 40 |
| | 40 | 53 | 1200 | 130 | 14 | 42 | 9 | 40 |
| $\frac{1}{3/4}$ | 45 | 58 | 1340 | 140 | 12 | 36 | 9 | 40 |
| 2 | 50 | 64 | 1730 | 150 | 12 | 36 | 9 | 40 |
| | 60 | 74 | 1950 | 180 | 12 | 36 | 9 | 40 |
| $\frac{2}{1/2}$ | 63 | 77 | 2030 | 190 | 12 | 36 | 9 | 40 |