

913042 牛奶管 VACUPRESS FOOD

多层热塑橡胶软管，内嵌镀锌钢丝螺旋，聚酯纤维

加强，用于抽吸和输送牛奶 输送食品的液体。

Multi-layer thermoplastic rubber hose with

embedded galvanised steel spiral with

polyester yarn reinforcement, for suction and delivery of milk.



商品详情

表面平滑度

SMOOTH SURFACE

柔韧性能

FLEXIBILITY

耐磨性能

ABRASION RESISTANCE

ISO 4649:<150 mm³

适用温度范围

TEMPERATURE RANGE

-25°C + 80°C

抗化学物质

CHEMICAL RESISTANCE

tabella PVC

抗压性能

CRUSHING RESISTANCE

根据 FDA 21 CFR 177.2600 par. “e” (含水食品)标准生产。

Produced according to FDA 21 CFR 177.2600 par. “e” (watery foodstuff).

内径 ID Inc	内径 ID mm	外径 OD mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS m/m	工作压力 WORKING PRESS bar		爆破压力 BURSTING PRESS bar	真空度 VACUUM m H2O	每卷长 度 COIL LENGTH mt
					20o	60o			
3/4	19	28	380	70	16	12	48	9	60
1	25	35.5	580	80	16	12	48	9	60
	30	40.5	650	85	13	9	39	9	60
1 1/4	32	42.5	730	90	13	9	39	9	60
	35	47	850	95	13	9	39	9	60
1 1/2	38	50	920	100	13	7	39	9	30
	40	52	970	110	10	7	30	9	30
1 3/4	45	57	1100	120	10	7	30	9	30

2	50	63	1280	130	10	7	30	9	30
	60	73	1550	160	10	7	30	9	30
$2\frac{1}{2}$	63	76	1600	180	10	7	30	9	30
3	76	91	2350	230	10	7	30	9	30
	80	95.5	2400	250	10	7	30	9	30
$3\frac{1}{2}$	90	105.5	2750	280	10	7	30	9	30
4	102	118.5	3100	310	10	6	30	9	30