

# 913043 耐真空化学馆 VACUPRESS

## CHEMI

多层热塑橡胶软管，内嵌镀锌钢丝螺旋，聚酯纤维加强，用于抽吸和输送腐蚀性液体。



Multi-layer thermoplastic rubber embedded galvanised steel spiral with polyester yarn reinforcement, for suction and delivery of aggressive liquids.

### 商品详情

表面平滑度 SMOOTH SURFACE	*****
柔韧性能 FLEXIBILITY	****
耐磨性能 ABRASION RESISTANCE	ISO 4649:<150 mm <sup>3</sup>
适用温度范围 TEMPERATURE RANGE	-25°C + 80°C
抗化学物质 CHEMICAL RESISTANCE	tabella PVC
抗压性能 CRUSHING RESISTANCE	***

内径 ID Inc	内径 ID mm	外径 OD mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS m/m	工作压力 WORKING PRESS bar		爆破压力 BURSTING PRESS bar	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
					20o	60o			
3/4	19	28	380	70	15	8	45	9	60
1	25	35.5	580	80	14	6	42	9	60
	30	40.5	650	85	10	6	30	9	60
1 1/4	32	42.5	700	90	10	6	30	9	60
	35	47	850	95	10	6	30	9	60
1 1/2	38	50	920	100	10	6	30	9	30
	40	52	970	110	10	6	30	9	30
1 3/4	45	57	1100	120	10	6	30	9	30

2	50	63	1280	130	10	5	30	9	30
	60	73	1550	160	9	4	27	9	30
2 1/2	63	76	1600	180	9	4	27	9	30
3	76	91	2350	230	8	4	24	9	30
	80	95.5	2400	250	8	4	24	9	30
3 1/2	90	105.5	2750	280	8	4	24	9	30
4	102	118.5	3100	310	7	3	21	9	30