

## 912980 METALFLEX I

柔软 PVC 管 ,内嵌钢丝螺旋 ,用于抽吸工业液体。

Soft PVC hose with embedded steel spiral for suction of industrial liquids.



### 商品详情：

表面平滑度

SMOOTH SURFACE

\*\*\*\*\*

柔韧性能

FLEXIBILITY

\*\*\*

耐磨性能

ABRASION RESISTANCE

\*\*\*

适用温度范围

TEMPERATURE RANGE

-5°C + 65°C

抗化学物质

CHEMICAL RESISTANCE

tabella PVC

抗压性能

CRUSHING RESISTANCE

\*\*\*

内径 ID Inc	内径 ID mm	外径 OD mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS m/m	工作压力 WORKING PRESS bar	爆破压力 BURSTING PRESS bar	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
3/8	10	15.5	140	25	7	21	8.5	60
	12	17.5	160	30	7	21	8.5	60
	14	19.5	175	35	6	18	8.5	60
5/8	16	21.5	190	40	6	18	8.5	60
	18	24	260	45	6	18	8.5	60
	20	26.5	280	55	5	15	8.5	60
1	25	32	450	65	5	15	8.5	60
	30	38	540	75	4.5	13.5	8.5	60
1 1/4	32	40	580	80	4.5	13.5	8.5	60
	35	43	630	85	4	12	8.5	60
1 1/2	38	46	685	95	4	12	8.5	30

	40	49	845	100	3	9	8.5	30
1 3/4	45	54	970	120	3	9	8	30
2	50	59	1060	135	3	9	8	30
	60	71.5	1650	170	2	6	8	30