

## 913066 SUPERFLEX PU LR

PU 软管，镀铜钢丝螺旋，用于抽吸和输送粉尘、木屑及粗糙材料。



Polyurethane hose with copper-plated steel spiral for suction and transport of dusts, chips and abrasive material.

### 商品详情

表面平滑度

SMOOTH SURFACE

\*\*

柔韧性能

FLEXIBILITY

\*\*\*\*\*

耐磨性能

ABRASION RESISTANCE

\*\*\*\*\*

适用温度范围

TEMPERATURE RANGE

-40°C + 90°C

抗化学物质

CHEMICAL RESISTANCE

tabella PU

抗压性能

CRUSHING RESISTANCE

\*\*

抗臭氧

OZONE RESISTANCE

\*\*\*\*\*

内径 ID Inc	内径 ID mm	壁厚 WALL THICKNESS mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS mm	螺旋间距 SPIRAL PITCH mm	螺旋直径 SPIRAL mm	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
	20	0.4	100	5	9.5	1.0	0.40	30
1	25	0.4	115	6	9.5	1.0	0.40	30
	30	0.4	130	7	14	1.0	0.30	30
	35	0.4	140	8	14	1.0	0.28	30
	40	0.4	150	10	14	1.0	0.25	30
1 3/4	45	0.4	170	12	14	1.0	0.23	30
2	50	0.4	185	13	18	1.2	0.20	15

	60	0.4	220	15	18	1.2	0.16	15
$\frac{2}{1/2}$	63	0.4	230	16	18	1.2	0.15	15
	70	0.4	330	18	18	1.4	0.14	15
3	75	0.4	350	19	18	1.4	0.10	15
	80	0.4	370	20	18	1.4	0.10	15
$\frac{3}{1/2}$	90	0.4	420	22	18	1.4	0.10	15
	100	0.4	480	20	23	1.6	0.09	15
	110	0.4	520	22	23	1.6	0.09	15
	120	0.4	550	24	23	1.6	0.09	15
	125	0.4	590	25	23	1.6	0.08	15
	130	0.4	610	26	23	1.6	0.08	15
	140	0.4	660	28	23	1.6	0.08	15
	150	0.5	700	30	30	1.8	0.06	15
	160	0.5	750	32	30	1.8	0.06	15
	170	0.5	780	34	30	1.8	0.06	15
	180	0.5	830	36	30	1.8	0.06	15
	200	0.5	920	40	30	1.8	0.05	15
	220	0.5	1070	45	30	1.8	0.05	15
	250	0.6	1250	50	36	2.0	0.04	15
	300	0.6	1500	60	36	2.0	0.03	10
	350	0.6	1750	70	36	2.0	0.03	10
	400	0.6	2000	80	36	2.0	0.02	10
	450	0.6	2300	90	36	2.0	0.01	10
	500	0.6	2500	100	36	2.0	0.01	10
	600	0.6	3000	120	36	2.0	0.01	10