

912810 SUPERFLEX PU MR SOFFIETTO

PU 软管，镀铜钢丝螺旋，用于抽吸和输送粉尘、木屑及粗糙材料。



Polyurethane hose with coil

商品详情

| | |
|------------------------------|--------------|
| 表面平滑度 SMOOTH SURFACE | ** * |
| 柔韧性能 FLEXIBILITY | ***** |
| 耐磨性能 ABRASION RESISTANCE | ***** |
| 适用温度范围 TEMPERATURE RANGE | -40°C + 90°C |
| 抗化学物质 CHEMICAL RESISTANCE | tabella PU |
| 抗压性能 CRUSHING RESISTANCE | ** * |
| 抗臭氧 OZONE RESISTANCE | ***** |

| 内径 ID Inc | 内径 ID mm | 壁厚 WALL THICKNESS mm | 重量 WEIGHT g/m | 弯曲半径 BENDING RADIUS mm | 螺旋间距 SPIRAL PITCH mm | 螺旋直径 SPIRAL mm | 真空度 VACUUM m H2O | 每卷长度 COIL LENGTH mt |
|-----------------|----------------|-------------------------------|---------------------|---------------------------------|-------------------------------|----------------------|------------------------|------------------------------|
| | 40 | 0.5 | 250 | 10 | 16 | 1.2×1.6 | 0.25 | 30 |
| 1 3/4 | 45 | 0.5 | 285 | 12 | 16 | 1.2×1.6 | 0.23 | 30 |
| 2 | 51 | 0.5 | 320 | 13 | 16 | 1.2×1.6 | 0.20 | 30 |
| | 60 | 0.5 | 370 | 15 | 16 | 1.2×1.6 | 0.16 | 30 |
| 2 1/2 | 63 | 0.5 | 390 | 16 | 16 | 1.2×1.6 | 0.15 | 30 |
| | 70 | 0.5 | 480 | 18 | 16 | 1.4×1.8 | 0.14 | 30 |
| 3 | 76 | 0.5 | 510 | 19 | 16 | 1.4×1.8 | 0.14 | 30 |
| | 80 | 0.5 | 540 | 20 | 16 | 1.4×1.8 | 0.10 | 30 |
| 3 1/2 | 90 | 0.5 | 600 | 23 | 16 | 1.4×1.8 | 0.09 | 30 |

| | | | | | | | | |
|----|-----|-----|------|-----|----|---------|------|----|
| 4 | 102 | 0.5 | 650 | 25 | 16 | 1.4×1.8 | 0.09 | 30 |
| | 110 | 0.5 | 700 | 28 | 16 | 1.4×1.8 | 0.09 | 30 |
| | 120 | 0.6 | 750 | 30 | 21 | 1.4×1.8 | 0.07 | 30 |
| 5 | 127 | 0.6 | 830 | 32 | 21 | 1.6×2.0 | 0.07 | 30 |
| | 130 | 0.6 | 850 | 33 | 21 | 1.6×2.0 | 0.07 | 30 |
| | 140 | 0.6 | 920 | 35 | 21 | 1.6×2.0 | 0.07 | 30 |
| 6 | 152 | 0.6 | 1020 | 38 | 21 | 1.6×2.0 | 0.05 | 30 |
| | 160 | 0.6 | 1200 | 40 | 21 | 1.8×2.2 | 0.05 | 30 |
| | 180 | 0.6 | 1300 | 45 | 21 | 1.8×2.2 | 0.05 | 30 |
| 8 | 203 | 0.6 | 1450 | 50 | 21 | 1.8×2.2 | 0.05 | 30 |
| 9 | 228 | 0.6 | 1600 | 58 | 21 | 1.8×2.2 | 0.05 | 30 |
| 10 | 254 | 0.6 | 2000 | 64 | 21 | 2.0×2.5 | 0.04 | 30 |
| 11 | 279 | 0.6 | 2200 | 70 | 21 | 2.0×2.5 | 0.04 | 15 |
| 12 | 305 | 0.6 | 2450 | 76 | 21 | 2.0×2.5 | 0.03 | 15 |
| 14 | 356 | 0.6 | 2850 | 88 | 21 | 2.0×2.5 | 0.03 | 15 |
| 16 | 406 | 0.6 | 3250 | 102 | 21 | 2.0×2.5 | 0.02 | 15 |