

## 915133 POLIPO 15 BAR OIL

柔软 PVC 管，PU 衬里，聚酯纤维加强，粘性

间层，用于压缩油、柴油及生物油。

Soft PVC hose with PU underlayer with

polyester yarn reinforcement and

adhesive middle layer, for pressurized

transfer of oil, diesel oil, bio diesel.



### 商品详情

表面平滑度

SMOOTH SURFACE

\*\*\*\*\*

柔韧性能

FLEXIBILITY

\*\*\*\*

耐磨性能

ABRASION RESISTANCE

\*\*\*

适用温度范围

TEMPERATURE RANGE

-10°C + 60°C

抗化学物质

CHEMICAL RESISTANCE

tabella PU

抗压性能

CRUSHING RESISTANCE

\*\*\*

| 内径<br>ID<br>mm | 外径<br>OD<br>mm | 重量<br>WEIGHT<br>g/m | 弯曲半径<br>BENDING<br>RADIUS<br>bar | 工作压力<br>WORKING<br>PRESS<br>bar<br>20°C | 工作压力<br>WORKING<br>PRESS<br>bar<br>40°C | 工作压力<br>WORKING<br>PRESS<br>bar<br>60°C | 每卷长度<br>COIL<br>LENGTH<br>mt |
|----------------|----------------|---------------------|----------------------------------|---|---|---|------------------------------|
| 19             | 26             | 350                 | 65                               | 15                                      | 10                                      | 6                                       | 50                           |
| 25             | 35             | 640                 | 100                              | 15                                      | 10                                      | 6                                       | 50                           |