

## 915097 JAMAICA S

柔韧 PVC 软管，能平躺放置，聚酯纤维加强，抗  
延展性，用于输送常规压缩液体。

Flexible layflat PVC hose, with polyester yarn  
reinforcement resistant to elongation, for  
pressurised delivery of liquids in general.



### 商品详情

#### 表面平滑度

SMOOTH SURFACE

\*\*\*\*\*

#### 柔韧性能

FLEXIBILITY

\*

#### 耐磨性能

ABRASION RESISTANCE

\*\*\*

#### 适用温度范围

TEMPERATURE RANGE

-5°C + 60°C

#### 抗化学物质

CHEMICAL RESISTANCE

tabella PVC

#### 抗压性能

CRUSHING RESISTANCE

\*

内径 ID Inc	内径 ID mm	外径 OD mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS bar	工作压力 WORKING PRESS bar 20°C	工作压力 WORKING PRESS bar 40°C	工作压力 WORKING PRESS bar 60°C	每卷长度 COIL LENGTH mt
1 1/2	38	40	175	2.5	1.5	1	7.5	100
	40	42	180	2.5	1.5	1	7.5	100
2	51	53	270	2.5	1.5	1	7.5	100
	60	63	300	2	1	0.5	6	100
2 1/2	63	66	310	2	1	0.5	6	100

3	76	79	380	2	1	0.5	6	100
	80	83	390	1.5	0.8	0.3	4.5	100
4	102	105	500	1.5	0.8	0.3	4.5	100