

911003 OREGON PU ET

PU 软管，PVC 筋骨螺旋，用于抽吸和输送粗糙材料、干燥食品。



Polyurethane polyether hose with PVC spiral,
for suction and transport of abrasive materials and dry foods.

商品详情

表面平滑度 SMOOTH SURFACE	*****
柔韧性能 FLEXIBILITY	*****
耐磨性能 ABRASION RESISTANCE	*****
适用温度范围 TEMPERATURE RANGE	-25°C + 85°C
抗化学物质 CHEMICAL RESISTANCE	tabella PU
抗压性能 CRUSHING RESISTANCE	*****
抗水解性能 CRUSHING RESISTANCE	60°C 温水下不水解 Resistant to hydrolysis in 60°C warm water.
抗微生物 MICROORGANISMS RESISTANCE	*****
抗臭氧 OZONE RESISTANCE	*****

符合 CE1935/2004 标准和 UE10/2011 标准关于接触干燥食品的规定。

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with dry foodstuff.

内径 ID Inc	外径 OD mm	壁厚 WALL THICKNESS mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS m/m	工作压力 WORKING PRESS bar	爆破压力 BURSTING PRESS bar	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
1	25	0.5	160	25	0.6	1.8	4	20
	30	0.6	190	30	0.6	1.8	4	20
1 1/4	32	0.6	195	32	0.6	1.8	4	20
	35	0.6	210	35	0.4	1.2	4	20
1 1/2	38	0.6	250	38	0.4	1.2	3	20
	40	0.6	280	40	0.4	1.2	3	20
1 3/4	45	0.6	320	45	0.4	1.2	3	20
2	50	0.7	390	50	0.4	1.2	3	20
	60	0.7	440	60	0.4	1.2	3	20
2 1/2	63	0.7	470	63	0.3	0.9	3	20
	70	0.7	600	70	0.3	0.9	3	20
	75	0.7	600	75	0.3	0.9	3	20
	80	0.7	650	80	0.2	0.6	3	20
3 1/2	90	0.8	750	90	0.2	0.6	3	20
	100	0.8	850	100	0.2	0.6	3	20
	110	0.8	1050	110	0.2	0.6	3	20
	120	0.8	1100	120	0.15	0.45	3	20
	125	0.8	1170	125	0.15	0.45	3	20
	130	0.8	1280	130	0.15	0.45	3	20
	140	0.9	1400	140	0.1	0.3	3	20
	150	0.9	1500	150	0.1	0.3	3	20
	160	0.9	1700	160	0.1	0.3	3	20
	180	0.9	2000	180	0.1	0.3	3	10
	200	0.9	2180	200	0.1	0.3	3	10
	250	1	2960	250	0.1	0.3	3	10
	300	1	3700	300	0.1	0.3	3	10