

911015 OREGON PU EST

PU 软管，PVC 螺旋，用于抽吸和输送粗糙材料及干燥食品。



Polyurethane polyester hose with PVC spiral, for suction and transport of abrasive materials and dry foods.

商品详情

| | |
|------------------------------|--------------|
| 表面平滑度 SMOOTH SURFACE | ***** |
| 柔韧性能 FLEXIBILITY | ***** |
| 耐磨性能 ABRASION RESISTANCE | ***** |
| 适用温度范围 TEMPERATURE RANGE | -25°C + 85°C |
| 抗化学物质 CHEMICAL RESISTANCE | tabella PU |
| 抗压性能 CRUSHING RESISTANCE | *** |
| 抗臭氧 OZONE RESISTANCE | ***** |

符合 CE1935/2004 标准和 UE10/2011 标准关于接触干燥食品的规定。

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with dry foodstuff.

| 内径 ID Inc | 外径 OD mm | 壁厚 WALL THICKNESS mm | 重量 WEIGHT g/m | 弯曲半径 BENDING RADIUS m/m | 工作压力 WORKING PRESS bar | 爆破压力 BURSTING PRESS bar | 真空度 VACUUM m H2O | 每卷长度 COIL LENGTH mt |
|-----------------|----------------|-------------------------------|---------------------|----------------------------------|---------------------------------|----------------------------------|------------------------|------------------------------|
| 1 | 25 | 0.5 | 160 | 25 | 0.6 | 1.8 | 4 | 20 |
| | 30 | 0.6 | 190 | 30 | 0.6 | 1.8 | 4 | 20 |
| 1 1/4 | 32 | 0.6 | 195 | 32 | 0.6 | 1.8 | 4 | 20 |
| | 35 | 0.6 | 210 | 35 | 0.4 | 1.2 | 4 | 20 |
| 1 1/2 | 38 | 0.6 | 250 | 38 | 0.4 | 1.2 | 3 | 20 |
| | 40 | 0.6 | 280 | 40 | 0.4 | 1.2 | 3 | 20 |

| | | | | | | | | |
|----------|-----|-----|------|-----|------|------|---|----|
| 1 3/4 | 45 | 0.6 | 320 | 45 | 0.4 | 1.2 | 3 | 20 |
| 2 | 50 | 0.7 | 390 | 50 | 0.4 | 1.2 | 3 | 20 |
| | 60 | 0.7 | 440 | 60 | 0.4 | 1.2 | 3 | 20 |
| 2 1/2 | 63 | 0.7 | 470 | 63 | 0.3 | 0.9 | 3 | 20 |
| | 70 | 0.7 | 600 | 70 | 0.3 | 0.9 | 3 | 20 |
| | 75 | 0.7 | 600 | 75 | 0.3 | 0.9 | 3 | 20 |
| | 80 | 0.7 | 650 | 80 | 0.2 | 0.6 | 3 | 20 |
| 3 1/2 | 90 | 0.8 | 750 | 90 | 0.2 | 0.6 | 3 | 20 |
| | 100 | 0.8 | 850 | 100 | 0.2 | 0.6 | 3 | 20 |
| | 110 | 0.8 | 1050 | 110 | 0.2 | 0.6 | 3 | 20 |
| | 120 | 0.8 | 1100 | 120 | 0.15 | 0.45 | 3 | 20 |
| | 125 | 0.8 | 1170 | 125 | 0.15 | 0.45 | 3 | 20 |
| | 130 | 0.8 | 1280 | 130 | 0.15 | 0.45 | 3 | 20 |
| | 140 | 0.9 | 1400 | 140 | 0.1 | 0.3 | 3 | 20 |
| | 150 | 0.9 | 1450 | 150 | 0.1 | 0.3 | 3 | 20 |
| | 160 | 0.9 | 1700 | 160 | 0.1 | 0.3 | 3 | 20 |
| | 180 | 0.9 | 2000 | 180 | 0.1 | 0.3 | 3 | 10 |
| | 200 | 0.9 | 2180 | 200 | 0.1 | 0.3 | 3 | 10 |
| | 250 | 1 | 2960 | 250 | 0.1 | 0.3 | 3 | 10 |
| | 300 | 1 | 3700 | 300 | 0.1 | 0.3 | 3 | 10 |