

911011 OREGON PU ET ANTISTATICO

PU 软管，PVC 螺旋，铜线防静电，抽吸和输送粗糙材料及干燥食品。



Polyurethane polyether hose with PVC

spiral, copper wire for antistatic rendering, for suction and transport of abrasive materials and dry foods.

商品详情

表面平滑度 SMOOTH SURFACE	*****
柔韧性能 FLEXIBILITY	*****
耐磨性能 ABRASION RESISTANCE	*****
适用温度范围 TEMPERATURE RANGE	-25°C + 85°C
抗化学物质 CHEMICAL RESISTANCE	tabella PU
抗压性能 CRUSHING RESISTANCE	***
防静电 ANTISTATIC	Resistenza trefolo 0,075 OHM/m
抗水解性能 CRUSHING RESISTANCE	60°C 温水下不水解 Resistant to hydrolysis in 60°C warm water.
抗微生物 MICROORGANISMS RESISTANCE	*****
抗臭氧 OZONE RESISTANCE	*****

符合 CE1935/2004 标准和 UE10/2011 标准规定, 接触干燥食品的介质需要通过在温度 70° C 对模拟液 E 进行 1 小时的测试。

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with dry foodstuff that requires a simulating liquid type E, specific migration tests performed at 70° C for 1 hours.

内径 ID Inc	外径 OD mm	壁厚 WALL THICKNESS mm	重量 WEIGHT g/m	弯曲半径 BENDING RADIUS m/m	工作压力 WORKING PRESS bar	爆破压力 BURSTING PRESS bar	真空度 VACUUM m H2O	每卷长度 COIL LENGTH mt
1	25	0.5	190	25	0.6	1.8	4	20
	30	0.6	210	30	0.6	1.8	4	20
1 1/4	32	0.6	240	32	0.6	1.8	4	20
	35	0.6	250	35	0.4	1.2	4	20
1 1/2	38	0.6	310	38	0.4	1.2	3	20
	40	0.6	330	40	0.4	1.2	3	20
1 3/4	45	0.6	370	45	0.4	1.2	3	20
2	50	0.7	440	50	0.4	1.2	3	20
	60	0.7	500	60	0.4	1.2	3	20
2 1/2	63	0.7	530	63	0.3	0.9	3	20
	70	0.7	660	70	0.3	0.9	3	20
	75	0.7	660	75	0.3	0.9	3	20
	80	0.7	740	80	0.2	0.6	3	20
3 1/2	90	0.8	810	90	0.2	0.6	3	20
	100	0.8	920	100	0.2	0.6	3	20
	110	0.8	1120	110	0.2	0.6	3	20
	120	0.8	1180	120	0.15	0.45	3	20
	125	0.8	1250	125	0.15	0.45	3	20
	130	0.8	1350	130	0.15	0.45	3	20
	140	0.9	1500	140	0.1	0.3	3	20
	150	0.9	1600	150	0.1	0.3	3	20
	160	0.9	1780	160	0.1	0.3	3	20
	180	0.9	2100	180	0.1	0.3	3	10
	200	0.9	2280	200	0.1	0.3	3	10